

WRT

Rider Electric Power Pallet Truck

■ Heavy duty end-control rider pallet truck ideal for manufacturing and large warehouse applications

CAPACITY

6000 lbs (2727 kg)

BATTERY

Compartment: 31.12" (790mm) x 13.12" (333mm) x 31.62" (803mm).
Anderson 175 Gray—A-11 min/max battery weight 975/1500 lbs
(443/682 kg).

SPEED

Variable from 0 mph up to 9.0 mph empty
Variable from 0 mph up to 6.5 mph loaded

WEIGHT

1528 lbs (695 kg) chassis only

TIRES AND WHEELS

DRIVE

10" x 4" (254 x 102mm) polyurethane

STABILITY CASTER WHEELS

2 - 3.9" x 2.5" (99 x 63.5mm) polyurethane

LOAD

2 - 3.25" x 6.5" (83 x 165mm) polyurethane

OPERATOR AREA - CONTROLS

The WRT 60 stand-up end control power pallet truck has a large operator platform which increases operator comfort and productivity. Careful location of ergonomic operator handle feature easy to use controls for travel, lift, lower and horn functions. All operator controls are accessible without having to lift the hand from the handle. Large thumb control lever for forward and reverse travel allows travel as a rider truck or walkie.

Microcellular rubber floor mat and angled power head cover are designed to allow easy operation with either hand and improved operator comfort.

Smooth urethane high speed grab bar for operator security with one touch high speed button.

ELECTRICAL

Heavy-duty, 24-Volt system for demanding warehouse applications. The programmable ZAPI traction control and matching drive motor provide high performance throughout the entire speed range.

Travel speed remains constant relative to throttle position regardless of load. Separately fused power control circuits, quick disconnect EPD power cut off, hour meter/battery discharge indicator combination gauge complete the system. Power configurations and diagnostic features are standard.

HYDRAULICS

Heavy duty pump motor with center mounted lift cylinder. Heavy-duty, pump unit, motor, hydraulic reservoir, solenoid, and gear pump. Integral pressure compensated flow control valve regulates lowering speeds.

DRIVE UNIT

Vertically mounted drive motor is directly mounted to gear housing. Oil bathed hypoid bevel gear drive train with tapered roller bearings transfers power to axle. State of the art optimized gear technology supplies advantages such as minimal envelope circle, zero maintenance, low noise level, high efficiency and high performance. Regenerative electromagnetic



brake is mounted on motor armature shaft multiplying the braking power through the transmission. Brake is applied when control arm is in the vertical or horizontal handle position. System features anti-roll back and neutral braking.

CASTER SYSTEM

Heavy duty spring loaded, articulating systems designed to stabilize truck performance and increase operator comfort.

FORK ASSEMBLY

Pallet entry slide allows easy pallet entry by lifting the fork up and over bottom board. Eight easily accessed grease zerks for ease of maintenance. Tapered extended fork tip design is available on double pallet handling models.

ACCESSIBILITY

Heavy duty composite two piece cover exposes major components for inspection and maintenance.

STANDARD EQUIPMENT

- 24-Volt regenerative braking
- Large AC traction motor
- Microcellular rubber floor mat
- Two piece powerhead cover
- Tapered fork tips w/entry skid plate
- Programmable performance travel/plugging/braking
- Ergonomic high speed bar




BLUE GIANT®
MATERIAL HANDLING DIVISION

Electric Forklifts

WRT Rider Electric Power Pallet Truck

BLUE GIANT®

Dimensions



Gradeability

Without Load 15%
With Load 8%

Travel Power Head First - Variable

Empty: 0 to 9.0 mph
Loaded: 0 to 6.5 mph

Travel Forks First - Variable

Empty: 0 to 7.1 mph
Loaded: 0 to 5.4 mph

Lowered Fork Height: 3.25" (82.55mm)

Maximum Lift Height: 5.5" (140mm)

Extended Fork Height: 8.25" (210mm)

Platform Step Height: 10.25" (260mm)



* For metric conversion multiply inches by 25.4.

Model #	Forks	Fork Width	Actual Fork Length	Turning Radius	Wheelbase	Overall Length	Grade Clearance	Weight (lbs)
		A	B	C	D	E	F	
Fork Dimensions: 27" Wide								
WRT60	27 x 36	27	35.5	68.9	55.8	80.1	38%	1175
WRT60	27 x 48	27	46.9	81.2	67.8	91.5	30%	1254
WRT60	27 x 60	27	59.5	59.8	67.8	104.1	25%	1354
WRT60	28 x 96	28	95.6	101.9	88.6	140.2	17%	1595
Fork Dimensions: 22" Wide								
WRT60	22 x 36	22	35.5	68.9	55.8	80.1	38%	1175
WRT60	22 x 48	22	46.9	81.2	67.8	91.5	30%	1254

² Extended-tip forks ³ Estimated shipping weight without battery.

*For metric conversion multiply inches by 25.4.



85 Heart Lake Road South
Brampton, Ontario, Canada L6W 3K2
Phone: 905-457-3900 • Fax: 905-457-2313
www.BlueGiant.com

AUTHORIZED DISTRIBUTOR

BLUE GIANT MATERIAL HANDLING DIVISION

BLUE GIANT offers a full line of Loading Dock Equipment including Dock Levelers, Vehicle Restraints, Dock Seals and Shelters and Material Handling Solutions. Concurrent with our continuing product improvement program, specifications are subject to change without notice. Please contact BLUE GIANT for latest information. Some features illustrated may be optional in certain market areas.

WORLD CLASS WORLD WIDE

2011/11/11