

## EPT-55 Series

An excellent heavy-duty hand pallet truck for customers who want performance and value.

### CAPACITY

5500 lbs (2500 kg)

### OPERATION

- 200 degree handle pivot.
- Only requires ten full strokes to reach maximum elevated height of 7.8" (198mm).
- Control handle has three position (raise/neutral/lower) fingertip control.
- Spring loaded handle returns to upright position automatically.
- Padded grip handle for comfort.

### HYDRAULICS

- Galvanized hydraulic pump includes an overload relief valve and lowering can be actuated by either hand or foot pedal release.

### FORKS / CHASSIS


- Climber rollers for easy entry into pallets.
- Exit rollers mounted on hanger bracket reduces wear and allows for easy exiting of pallets.
- Heavy duty frame constructed of one-piece formed channel.
- Adjustable push rods allow for adjustment to roller height.
- Hangers are constructed of cast iron for greater strength and longevity.
- Easy maintenance—grease fitting and bushings at all pivot points.
- Frame is powder coat paint.

### WARRANTY

- Two year structural and two year hydraulic pump warranty.



Comfort Grip and Easy Access Controls



Galvanized Pump



Entry / Exit Rollers

Designation	Model		EPT55 / 27 x 48		Wheels and Rollers	Steering Wheel	Polyurethane on Steel Hub	7" dia. x 2"	
		Load Capacity		5500 lb / 2500 kg					178mm dia. x 51mm
Chassis Dimensions	Pallet Forks	Lowered Height	2.9"	73.66mm	Performance	Load Rollers	Polyurethane	2.9" dia. x 3.6"	
		Fork Length	48"	1219mm				73mm dia. x 91mm	
		Fork Width	6.25"	159mm		Turning Radius	52.5" (1334mm)		
		Overall Fork Widths	20.5" or 27"	520mm - 686mm		Strokes to attain maximum lift	10 full		
	Raised Fork Height	7.8"	198mm	Steering pivot range (degrees)		200°			
	Approximate Shipping Weight		165 lbs	75 kg		Type of pump control - lift / release	Hand / Hand and Foot Release		
						Pallet entry assist type	Roller		